## NSN 5930-01-342-6740

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-342-6740

**Thread Class:** 

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Vibration resistant

Overall Length:

4.875 inches

**Overall Height:** 

3.000 inches

**Overall Width:** 

3.000 inches

**Individual Section Quantity:** 

6

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:** 

1.156 inches single mounting facility

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level350.0 highest dc voltage rating at sea level120.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Terminal Type:** 

Tab w/screw

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Contact Load Current Rating:** 

10.0 amperes inductive load ac at sea level and 10.0 amperes resistive load ac at sea level 2.0 amperes inductive load highest dc voltage rating at sea level and 2.0 amperes resistive load highest dc voltage rating at sea level 10.0 amperes inductive load lowest dc voltage rating at sea level and 10.0 amperes resistive load lowest dc voltage rating at sea level

**Style Designator:** 

Tap, circuit selector

## **Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

## NSN 5930-01-342-6740

Rotary Switch - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-s-15291/2 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0