

View Online at <https://aerobasegroup.com/nsn/5930-01-342-8924>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

1.270 inches

**Overall Height:**

Between 2.792 inches and 2.852 inches

**Overall Width:**

0.635 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.270 inches

**Body Width:**

0.635 inches

**Body Height:**

1.662 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

Between 0.660 inches and 0.720 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 wire lead

**Specification Data:**

96906-ms27722 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0