

View Online at <https://aerobasegroup.com/nsn/5930-01-343-0841>

Thread Class:

2a single mounting facility

Thread Length:

0.417 inches single mounting facility and 0.457 inches single mounting facility

Overall Length:

2.937 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.215 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.417 inches single actuator and 0.457 inches single actuator

Overall Diameter:

Between 1.152 inches and 1.172 inches

Individual Section Quantity:

4

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level 250.0 milliamperes inductive load dc at sea level and 1.25 amperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surfaces gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0