

View Online at <https://aerobasegroup.com/nsn/5930-01-343-4444>

Thread Class:

2a single mounting facility

Thread Length:

0.297 inches single mounting facility

Overall Height:

1.530 inches

Overall Width:

1.375 inches

First Flat Length:

0.230 inches single actuator and 0.250 inches single actuator

Flat Height:

0.195 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.265 inches single actuator

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

2 1st section front

Throw Quantity:

5 1st section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Rotor Through Connection Quantity:

2 1st section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 1st section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0