NSN 5930-01-344-0143

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-344-0143

Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
2.360 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
0.960 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
Yellow single actuator and yellow single actuator
Illuminated Actuator Color:
Yellow single actuator and yellow single actuator
Actuator Inscription:
Helo clr/on single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit

NSN 5930-01-344-0143

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0