NSN 5930-01-344-0144

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-344-0144

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight and dustproof

Overall Length:

2.360 inches

Overall Height:

0.960 inches

Overall Width:

0.960 inches

Body Width:

0.960 inches

Body Height:

0.960 inches

Case Material:

Metal

Actuator Length:

-----j---

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.275 inches

Actuator Width:

0.620 inches

Actuator Color:

Blue single actuator and blue single actuator

Illuminated Actuator Color:

Blue single actuator and blue single actuator

Actuator Inscription:

Day/night single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

Between 1.720 inches and 1.880 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-344-0144

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0