## NSN 5930-01-344-4942

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-344-4942

De de Code
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.120 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Length:
2.850 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.640 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.640 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Lamp test single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Screw clamp and panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action single switch unit

## NSN 5930-01-344-4942

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

S	рe	cial	Fe	atι	ire	s:
---	----	------	----	-----	-----	----

Inscription appears clear when illuminated

**Precious Material And Location:** 

Contact surfaces silver

**Terminal Type And Quantity:** 

6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0