## NSN 5930-01-344-5621

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-344-5621

Panel mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.120 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Length:
2.850 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.640 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.640 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Lamp test single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Screw clamp and panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
4 pole, double throw, two positions momentary single switch unit

## NSN 5930-01-344-5621

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special	Features:
---------	-----------

Inscription appears clear when illuminated

**Precious Material And Location:** 

Contact surfaces silver

**Terminal Type And Quantity:** 

6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0