

View Online at <https://aerobasegroup.com/nsn/5930-01-345-0200>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof and moisture resistant

**Overall Length:**

Between 2.391 inches and 2.537 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.084 inches single actuator and 0.104 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.355 inches single actuator and 0.395 inches single actuator

**Overall Diameter:**

Between 0.735 inches and 0.765 inches

**Individual Section Quantity:**

4

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

150.0 milliamperes resistive load ac at sea level 75.0 milliamperes inductive load dc at sea level and 250.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Terminal and contact and common plate surfaces gold and terminal and contact and common plate surfaces silver

**Precious Material:**

Gold and silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0