NSN 5930-01-345-4174

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-345-4174

Thread Length:

0.375 inches 2nd mounting facility

Shaft Length:

0.375 inches 1st actuator 0.250 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock0.531 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clocktab at 9: 00 o'clock

End Application:

6625-01-250-9594 generator, signa

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

7 single section periphery

Mounting Method:

Printed circuit 1st mounting facilitythreaded bushing 2nd mounting facility

Features Provided:

Variable resistor

Switch Actuator Indexing Position Quantity:

7 all actuators

Shaft Type:

Round, hollowed 1st actuatorround 2nd actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Adjustable stop all actuators

Style Designator:

Wafer, printed board, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-345-4174Rotary Switch - Page 2 of 2



Fiig:

A052b0