

View Online at <https://aerobasegroup.com/nsn/5930-01-345-4175>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

3.285 inches

Overall Height:

2.167 inches

Overall Width:

1.146 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

3.115 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

6625-01-250-9594 generator, signa

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Lever all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 1st actuator2 2nd actuator10 3rd actuator10 4th actuator10 5th actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

1st section0, 1 2nd section0, 1, 2, 3, 4, 5, 6, 7, 8, 9 3rd section0, 1, 2, 3, 4, 5, 6, 7, 8, 9 4th section0, 1, 2, 3, 4, 5, 6, 7, 8, 9 5th section

Contact Arrangement Truth Table:

Special 1st sectionspecial 2nd sectionbcd with even bit parity, 1 pole - 10 positions 3rd sectionbcd with even bit parity, 1 pole - 10 positions
4th sectionbcd with even bit parity, 1 pole - 10 positions 5th section

Special Truth Table Identification:

01963-4 1st section01963-special 0-1 2nd section

Color:

Black each bodyblack each indicator backgroundwhite each indicator marking

Precious Material And Location:

Printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0