## NSN 5930-01-345-5585

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-345-5585 **Thread Class:** 2a **Body Style:** Printed circuit **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.127 inches **Overall Height:** 0.500 inches **Overall Width:** 0.270 inches **Bushing Length:** 0.280 inches **Body Length:** 0.410 inches **Body Width:** 0.270 inches **Body Height:** 0.500 inches **Case Material:** Plastic **Actuator Style:** Round, flush **Actuator Diameter:** 0.122 inches **Actuator Height:** 0.248 inches **Maximum Voltage Rating In Volts:** 28.0 dc and 120.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing and printed circuit Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.250 inches

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:** 

1.000 amperes resistive dc and 1.000 amperes resistive ac

## NSN 5930-01-345-5585

Push Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contact and terminal surfaces gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A053a0