

View Online at <https://aerobasegroup.com/nsn/5930-01-345-6302>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Driptight and shock proof and vibration resistant

**Overall Length:**

2.960 inches

**Overall Height:**

0.740 inches

**Overall Width:**

0.990 inches

**Body Width:**

0.990 inches

**Body Height:**

0.740 inches

**Actuator Length:**

0.920 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

1.510 inches

**Actuator Width:**

0.680 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

Green single actuator and white single actuator

**Actuator Inscription:**

On line/form feed single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

Between 1.380 inches and 1.450 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Horizontal split lens and rfi shielding

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

**Precious Material And Location:**

Terminal surfaces gold

**Terminal Type And Quantity:**

12 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0