NSN 5930-01-345-6302

Hazardous Locations/environmental Protection:Driptight and shock proof and vibration resistant

Push Switch - Page 1 of 2

Body Style:Panel mounted

Overall Length:
2.960 inches
Overall Height:
0.740 inches
Overall Width:
0.990 inches



View Online at https://aerobasegroup.com/nsn/5930-01-345-6302

Body Width:
0.990 inches
Body Height:
0.740 inches
Actuator Length:
0.920 inches
Actuator Style:
Rectangular
Actuator Height:
1.510 inches
Actuator Width:
0.680 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and white single actuator
Actuator Inscription:
On line/form feed single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.380 inches and 1.450 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens and rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

NSN 5930-01-345-6302

Push Switch - Page 2 of 2



Precious Material And Location:
Terminal surfaces gold

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0