

View Online at <https://aerobasegroup.com/nsn/5930-01-345-7218>

Thread Class:

2a single threaded stud

Overall Length:

3.360 inches

Fragility Factor:

Moderately rugged

End Application:

Pacer dawn

Pressure Switch Type:

Differential

Width Across Flats:

1.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit

Mounting Method:

Threaded stud

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch gage

Thread Size:

1.562 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

180.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes inductive load single voltage and 3.0 amperes lamp load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

14.00 actuation point pounds per square inch and 15.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0