

View Online at <https://aerobasegroup.com/nsn/5930-01-345-7219>

**Thread Class:**

2a single threaded stud

**Overall Length:**

3.360 inches

**Fragility Factor:**

Moderately rugged

**Pressure Switch Type:**

Differential

**Width Across Flats:**

1.750 inches

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 350.0 degrees fahrenheit

**Mounting Method:**

Threaded stud

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

120.00 pounds per square inch gage

**Thread Size:**

1.562 inches single threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

180.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

3.0 amperes inductive load single voltage and 3.0 amperes lamp load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

3.00 actuation point pounds per square inch and 2.50 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unjf single threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0