NSN 5930-01-345-9986

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-345-9986 **Thread Class:** 2a **Body Style: Bushing mount Overall Length:** 0.500 inches **Overall Height:** 1.330 inches **Overall Width:** 0.270 inches **Bushing Length:** 0.280 inches **Body Length:** 0.500 inches **Body Width:** 0.270 inches **Body Height:** 0.350 inches **Case Material:** Plastic **Actuator Style:** Rectangular **Actuator Height:** 0.450 inches **Actuator Width:** 0.100 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position momentary **Maximum Voltage Rating In Volts:** 20.0 ac and 20.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:**

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.0 milliamperes resistive ac and 20.0 milliamperes resistive dc

NSN 5930-01-345-9986

Toggle Switch - Page 2 of 2



| Precious | Material | ∆nd I | Location: |
|----------|------------|-------|------------|
| riecious | ivialeriai | Allu | LUCALIUII. |

Contact and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0