

View Online at <https://aerobasegroup.com/nsn/5930-01-346-0595>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

Between 4.740 inches and 4.790 inches

**Overall Height:**

2.167 inches

**Overall Width:**

1.146 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

8

**Longest Horizontal Distance Between Mounting Centers:**

4.570 inches single mounting facility and 4.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**End Application:**

6625-01-250-9594 generator, signa

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Lever all actuators

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 16 positions each section

**Color:**

Black each bodyblack each indicator backgroundwhite each indicator marking

**Precious Material And Location:**

Printed circuit board circuit surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0