

View Online at <https://aerobasegroup.com/nsn/5930-01-346-0595>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

Between 4.740 inches and 4.790 inches

Overall Height:

2.167 inches

Overall Width:

1.146 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

8

Longest Horizontal Distance Between Mounting Centers:

4.570 inches single mounting facility and 4.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

End Application:

6625-01-250-9594 generator, signa

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Lever all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section

Contact Arrangement Truth Table:

Bcd, 1 pole - 16 positions each section

Color:

Black each bodyblack each indicator backgroundwhite each indicator marking

Precious Material And Location:

Printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0