

View Online at <https://aerobasegroup.com/nsn/5930-01-346-1677>

Thread Class:

2b

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.510 inches

Overall Height:

Between 1.594 inches and 1.604 inches

Overall Width:

0.275 inches

Bushing Length:

0.390 inches

Body Length:

0.510 inches

Body Width:

0.275 inches

Body Height:

0.440 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.218 inches

Actuator Height:

Between 0.604 inches and 0.614 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-s-83731/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0