NSN 5930-01-346-2962

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-346-2962

Inside Diameter:

0.250 inches single connection

Overall Length:

4.000 inches

Outside Diameter:

0.540 inches single connection

Overall Height:

6.062 inches

Overall Width:

2.343 inches

Mounting Slot Width:

0.312 inches

Body Height:

4.000 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

10000.00 pounds per square inch

Thread Size:

0.250 inches single threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load first voltage15.0 amperes resistive load second voltage15.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+200.00/+3000.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw with scale

NSN 5930-01-346-2962

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

125.0 ac at sea level first voltage250.0 ac at sea level second voltage480.0 ac at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage60.0 second voltage60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single threaded hole

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0