NSN 5930-01-346-7547

Code Indicating Wheel Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-346-7547 |
|--|
| Hazardous Locations/environmental Protection: |
| Humidity resistant and moisture resistant and vibration resistant |
| Overall Length: |
| 0.790 inches |
| Overall Height: |
| 0.555 inches |
| Overall Width: |
| 0.790 inches |
| Individual Section Quantity: |
| 1 |
| Operating Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| End Application: |
| 4865-01-299-5859 countermeasures |
| Mounting Method: |
| Printed circuit single mounting facility |
| Actuator Type: |
| Thumbwheel single actuator |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 10 single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Load Current Rating: |
| 125.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section |
| Contact Arrangement Truth Table: |
| Bcd, 1 pole - 10 positions single section |
| Color: |
| Black single bodyblack single indicator backgroundwhite single indicator marking |
| Precious Material And Location: |
| Contact and printed circuit board circuit surfaces gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Miniature panel mount |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5930-01-346-7547

Code Indicating Wheel Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0