NSN 5930-01-346-7868

Push Switch - Page 1 of 2



Thread Class: 2a Body Style: Bushing mounted Overall Length: 1.500 inches Overall Height: 1.592 inches Overall Width: 0.515 inches Bushing Length:
Body Style: Bushing mounted Overall Length: 1.500 inches Overall Height: 1.592 inches Overall Width: 0.515 inches
Bushing mounted Overall Length: 1.500 inches Overall Height: 1.592 inches Overall Width: 0.515 inches
Overall Length: 1.500 inches Overall Height: 1.592 inches Overall Width: 0.515 inches
1.500 inches Overall Height: 1.592 inches Overall Width: 0.515 inches
Overall Height: 1.592 inches Overall Width: 0.515 inches
1.592 inches Overall Width: 0.515 inches
Overall Width: 0.515 inches
0.515 inches
Bushing Length:
0.562 inches
Body Length:
0.984 inches
Body Width:
0.515 inches
Body Height:
0.468 inches
Case Material:
Plastic
Actuator Style:
Round
Actuator Diameter:
0.406 inches
Actuator Height:
0.437 inches
Actuator Color:
Silver single actuator
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Features Provided: Full display lens
Full display lens
Full display lens Thready Qty Per Inch (tpi):
Full display lens Thready Qty Per Inch (tpi): 32

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-346-7868

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac and 1.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0