NSN 5930-01-346-9690

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-346-9690

Thread	Class:
--------	--------

2a 1st mounting facility2a 2nd mounting facility

Thread Length:

0.190 inches 1st mounting facility 0.440 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

10.500 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

12

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

01040-11

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.810 inches 1st mounting facility

Mounting Method:

Base 1st mounting facility and threaded stud 1st mounting facilitythreaded bushing 2nd mounting facility

Features Provided:

Actuator knob and dummy terminal

Thread Size:

0.190 inches 1st mounting facility 0.625 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular 1st mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

NSN 5930-01-346-9690

Rotary Switch - Page 2 of 2



Contact Load Current Rating: 10.0 amperes resistive load ac at sea level Precious Material And Location: Contact surfaces silver Precious Material: Silver Style Designator: Tap, circuit selector Thread Series Designator: Unf 1st mounting facilityunef 2nd mounting facility Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A052b0