

View Online at <https://aerobasegroup.com/nsn/5930-01-347-1583>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Height:

8.781 inches

Overall Width:

4.062 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Tempurature Sensing Element Type:

Bulb

Operating Tempurature Rating:

188.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load first voltage12.0 amperes resistive load second voltage8.0 amperes resistive load third voltage500.0 milliamperes resistive load fourth voltage250.0 milliamperes resistive load fifth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+130.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage115.0 dc at sea level fourth voltage230.0 dc at sea level fifth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0