

View Online at <https://aerobasegroup.com/nsn/5930-01-347-1583>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Height:**

8.781 inches

**Overall Width:**

4.062 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Mounting Facility Centers:**

5.250 inches

**Tempurature Sensing Element Type:**

Bulb

**Operating Tempurature Rating:**

188.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load first voltage12.0 amperes resistive load second voltage8.0 amperes resistive load third voltage500.0 milliamperes resistive load fourth voltage250.0 milliamperes resistive load fifth voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+60.00/+130.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage115.0 dc at sea level fourth voltage230.0 dc at sea level fifth voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0