

View Online at <https://aerobasegroup.com/nsn/5930-01-347-1589>

Thread Class:

2a 1st mounting facility 2b 2nd mounting facility

Thread Length:

0.440 inches 1st mounting facility

Overall Length:

3.090 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing 1st mounting facility threaded hole 2nd mounting facility

Features Provided:

Actuator knob and dummy terminal

Thready Qty Per Inch (tpi):

24 2nd mounting facility

Thread Size:

0.625 inches 1st mounting facility 0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facilityunc 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0