

View Online at <https://aerobasegroup.com/nsn/5930-01-347-1591>

Overall Length:

6.438 inches

Overall Height:

2.562 inches

Overall Width:

2.625 inches

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.687 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level600.0 highest dc voltage rating at sea level24.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

40.0 amperes resistive load highest ac voltage rating at sea level and 0.3 amperes inductive load highest ac voltage rating at sea level40.0 amperes resistive load lowest ac voltage rating at sea level and 24.0 amperes inductive load lowest ac voltage rating at sea level400.0 milliamperes resistive load highest dc voltage rating at sea level and 300.0 milliamperes inductive load highest dc voltage rating at sea level10.0 amperes resistive load lowest dc voltage rating at sea level and 8.0 amperes inductive load lowest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: