

View Online at <https://aerobasegroup.com/nsn/5930-01-347-1591>

**Overall Length:**

6.438 inches

**Overall Height:**

2.562 inches

**Overall Width:**

2.625 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.875 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.687 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

600.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level600.0 highest dc voltage rating at sea level24.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

40.0 amperes resistive load highest ac voltage rating at sea level and 0.3 amperes inductive load highest ac voltage rating at sea level40.0 amperes resistive load lowest ac voltage rating at sea level and 24.0 amperes inductive load lowest ac voltage rating at sea level400.0 milliamperes resistive load highest dc voltage rating at sea level and 300.0 milliamperes inductive load highest dc voltage rating at sea level10.0 amperes resistive load lowest dc voltage rating at sea level and 8.0 amperes inductive load lowest dc voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**