## NSN 5930-01-347-2131

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-347-2131

**Thread Class:** 

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Corrosion resistant

**Overall Diameter:** 

3.750 inches

**Individual Section Quantity:** 

2

**Knob Manufacturer Code:** 

82121

**Knob Manufacturer Part Number:** 

02000-4-1

**Longest Horizontal Distance Between Mounting Centers:** 

2.300 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.300 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Makes before breaks each section periphery

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Rotor and stator surfaces silver

## NSN 5930-01-347-2131

Rotary Switch - Page 2 of 2



Precious Material:
Silver
Style Designator:
Tap, circular frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0