

View Online at <https://aerobasegroup.com/nsn/5930-01-347-2138>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Moisture proof and shock resistant

Body Width:

0.740 inches

Body Height:

0.740 inches

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Height:

1.645 inches

Actuator Width:

0.740 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Red single actuator and amber single actuator

Actuator Inscription:

Vts/irr single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.060 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Horizontal split lens

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc

Special Features:

8008a1c2d2j4l125m2n (ra) 16-vts/irr

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0