

View Online at <https://aerobasegroup.com/nsn/5930-01-347-4086>

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

5.520 inches

**Overall Height:**

2.160 inches

**Overall Width:**

2.140 inches

**Mounting Slot Width:**

0.142 inches

**Body Length:**

4.390 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.560 inches

**Longest Vertical Distance Between Mounting Centers:**

2.940 inches

**Temperature Sensing Element Type:**

Bulb

**Operating Temperature Rating:**

140.0 degrees fahrenheit

**Mounting Method:**

Base and slot

**Features Provided:**

Integral knob

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

16.0 amperes resistive load first voltage9.2 amperes resistive load second voltage8.0 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+30.00/+110.00 actuation point degrees fahrenheit and +26.50/+106.50 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point knob with scale and external deactuation point knob with scale

**Contact Voltage Rating In Volts:**

120.0 ac at sea level first voltage208.0 ac at sea level second voltage240.0 ac at sea level third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0