NSN 5930-01-347-4086

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-347-4086

Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
5.520 inches
Overall Height:
2.160 inches
Overall Width:
2.140 inches
Mounting Slot Width:
0.142 inches
Body Length:
4.390 inches
Longest Horizontal Distance Between Mounting Centers:
1.560 inches
Longest Vertical Distance Between Mounting Centers:
2.940 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
140.0 degrees fahrenheit
Mounting Method:
Base and slot
Features Provided:
Integral knob
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
16.0 amperes resistive load first voltage9.2 amperes resistive load second voltage8.0 amperes resistive load third voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+30.00/+110.00 actuation point degrees fahrenheit and +26.50/+106.50 deactuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point knob with scale and external deactuation point knob with scale

Contact Voltage Rating In Volts:
120.0 ac at sea level first voltage208.0 ac at sea level second voltage240.0 ac at sea level third voltage

NSN 5930-01-347-4086

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0