

View Online at <https://aerobasegroup.com/nsn/5930-01-347-4096>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

0.620 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.160 inches and 0.220 inches

**Overall Height:**

0.690 inches

**Overall Width:**

0.320 inches

**Body Length:**

0.620 inches

**Body Width:**

0.320 inches

**Body Height:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.077 inches and 0.097 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.060 inches

**Actuator Height:**

0.070 inches

**Actuator Free Position Height:**

0.475 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

0.050 pretravel inches and 0.004 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 1.000 amperes lamp dc and 2.500 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 1.000 amperes lamp ac and 1.500 amperes motor ac

**Special Features:**

Terminal wires are white

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0