

View Online at <https://aerobasegroup.com/nsn/5930-01-347-5447>

Inside Diameter:

0.125 inches single connection

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Mounting Facility Centers:

2.050 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

12000.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

4.0 amperes resistive load first voltage 4.0 amperes resistive load second voltage 3.0 amperes inductive load third voltage and 5.0 amperes lamp load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+300.00/+3000.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage 115.0 ac at sea level second voltage 30.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage 60.0 second voltage

Media For Which Designed:

Liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0