

View Online at <https://aerobasegroup.com/nsn/5930-01-347-5447>

**Inside Diameter:**

0.125 inches single connection

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Distance Between Mounting Facility Centers:**

2.050 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -20.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

12000.00 pounds per square inch

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

4.0 amperes resistive load first voltage 4.0 amperes resistive load second voltage 3.0 amperes inductive load third voltage and 5.0 amperes lamp load third voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+300.00/+3000.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage 115.0 ac at sea level second voltage 30.0 dc at sea level third voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 first voltage 60.0 second voltage

**Media For Which Designed:**

Liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0