

View Online at <https://aerobasegroup.com/nsn/5930-01-347-6443>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

1.000 inches

Bushing Length:

0.540 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.060 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.280 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 2.000 amperes inductive dc

Test Data Document:

81349-mil-s-5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Specification Data:

81349-mil-s-5594/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0