

View Online at <https://aerobasegroup.com/nsn/5930-01-347-6446>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

0.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.160 inches and 0.220 inches

Overall Height:

0.690 inches

Overall Width:

0.320 inches

Body Length:

0.620 inches

Body Width:

0.320 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

Between 0.077 inches and 0.097 inches

Actuator Style:

Round

Actuator Diameter:

0.060 inches

Actuator Height:

0.070 inches

Actuator Free Position Height:

0.475 inches

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.004 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 1.000 amperes lamp dc and 2.500 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 1.000 amperes lamp ac and 1.500 amperes motor ac

Special Features:

Terminal wires are gray

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0