

View Online at <https://aerobasegroup.com/nsn/5930-01-348-0243>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.265 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

1.050 inches

**First Flat Length:**

0.265 inches single actuator

**Flat Height:**

0.104 inches single actuator

**Shaft Diameter:**

0.126 inches single actuator

**Shaft Length:**

0.390 inches single actuator

**Overall Diameter:**

0.515 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

22.0 degrees single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load ac at sea level 125.0 milliamperes resistive load dc at sea level and 75.0 milliamperes inductive load dc at sea level

**Special Features:**

Fixed stop between the last and first position of switches; panel and shaft seals

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0