## NSN 5930-01-348-0372

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-348-0372

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.970 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.490 inches and 0.510 inches
Overall Height:
1.093 inches
Overall Width:
0.700 inches
Body Length:
Between 0.830 inches and 0.870 inches
Body Width:
0.700 inches
Body Height:
0.803 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
Between 0.122 inches and 0.128 inches
Actuator Style:
Round
Actuator Diameter:
0.109 inches
Actuator Free Position Height:
0.300 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac
Precious Material And Location:
Terminal surfaces silver

**Terminal Type And Quantity:** 2 wire lead

## NSN 5930-01-348-0372

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0