NSN 5930-01-348-2776



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-348-2776 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.500 inches **Overall Height:** 1.165 inches **Overall Width:** 0.314 inches **Bushing Length:** 0.350 inches **Body Length:** 0.500 inches

Body Width:
0.270 inches
Body Height:
0.410 inches

Case Material: Plastic

Actuator Style:

Round

Actuator Diameter:

0.310 inches

0.310 11101165

Actuator Height:

0.250 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 120.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Full display lens

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

NSN 5930-01-348-2776

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.0 milliamperes resistive dc and 1.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0