## NSN 5930-01-348-2776



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-348-2776 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.500 inches **Overall Height:** 1.165 inches **Overall Width:** 0.314 inches **Bushing Length:** 0.350 inches **Body Length:** 0.500 inches

Body Width:
0.270 inches
Body Height:
0.410 inches

Case Material: Plastic

Actuator Style:

Round

Actuator Diameter:

0.310 inches

0.310 11101165

**Actuator Height:** 

0.250 inches

**Actuator Color:** 

Black single actuator

**Maximum Voltage Rating In Volts:** 

28.0 dc and 120.0 ac

**Inclosure Type:** 

Fully enclosed

**Mounting Method:** 

Threaded bushing

**Features Provided:** 

Full display lens

Thready Qty Per Inch (tpi):

40

**Thread Size:** 

0.250 inches

# NSN 5930-01-348-2776

Push Switch - Page 2 of 2



### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

20.0 milliamperes resistive dc and 1.000 amperes resistive ac

### **Precious Material And Location:**

Contact and terminal surfaces gold and contacts silver

**Unable To Decode:** 

Unable to decode and unable to decode

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0