

View Online at <https://aerobasegroup.com/nsn/5930-01-348-4280>

Thread Class:

2a single mounting facility

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

Overall Length:

2.165 inches

First Flat Length:

0.230 inches all actuators and 0.270 inches all actuators

Flat Height:

0.219 inches 1st actuator 0.086 inches 2nd actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.251 inches 1st actuator 0.123 inches 2nd actuator and 0.126 inches 2nd actuator

Shaft Length:

0.355 inches 1st actuator and 0.395 inches 1st actuator 0.750 inches 2nd actuator

Overall Diameter:

Between 0.676 inches and 0.702 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise all actuators and counterclockwise all actuators

Switch Actuator Indexing Position Quantity:

3 all actuators

Shaft Type:

Round, flatted w/through hole 1st actuator round, flatted 2nd actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

36.0 degrees all actuators

Detent Rotational Torque Range:

+0.250/+2.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Adjustable stop all actuators

Contact Load Current Rating:

150.0 milliamperes resistive load ac at sea level 30.0 milliamperes inductive load dc at sea level and 200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Terminal surfaces and contacts silver and contact and terminal surfaces gold

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0