NSN 5930-01-348-4285

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-348-4285

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Shock resistant and vibration resistant |
| Overall Length: |
| 1.652 inches |
| Body Diameter: |
| 0.629 inches |
| Body Length: |
| 1.082 inches |
| Overall Diameter: |
| 0.629 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.354 inches |
| Actuator Height: |
| 0.570 inches |
| Maximum Voltage Rating In Volts: |
| 220.0 dc and 250.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 100.0 milliamperes resistive dc and 5.000 amperes resistive ac |
| Precious Material And Location: |
| Contact surfaces gold and contacts silver |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Fiig:

A053a0

Demilitarization: