

View Online at <https://aerobasegroup.com/nsn/5930-01-348-5049>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.190 inches

Outside Diameter:

0.125 inches single connection

Overall Height:

5.250 inches

Overall Width:

2.500 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

2.620 inches

Longest Vertical Distance Between Mounting Centers:

2.440 inches

End Application:

4610-01-219-8707 water purification equipment set

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.60/+15.00 actuation point pounds per square inch gage and +0.50/+14.20 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0