

View Online at <https://aerobasegroup.com/nsn/5930-01-348-5049>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.190 inches

**Outside Diameter:**

0.125 inches single connection

**Overall Height:**

5.250 inches

**Overall Width:**

2.500 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.620 inches

**Longest Vertical Distance Between Mounting Centers:**

2.440 inches

**End Application:**

4610-01-219-8707 water purification equipment set

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -20.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

400.00 pounds per square inch gage

**Thread Size:**

0.125 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.60/+15.00 actuation point pounds per square inch gage and +0.50/+14.20 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0