## NSN 5930-01-348-7198

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-348-7198

| View Online at https://aerobasegroup.com/nsn/5930-01-348-7198  |
|--|
| Body Style:  |
| Panel mounted  |
| Hazardous Locations/environmental Protection:  |
| Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof                          |
| Overall Length:  |
| 3.060 inches   |
| Overall Height:  |
| 0.740 inches   |
| Overall Width:   |
| 0.740 inches   |
| Body Width:  |
| 0.740 inches   |
| Body Height:   |
| 0.740 inches   |
| Case Material:   |
| Metal  |
| Actuator Length:   |
| 0.740 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Width:  |
| 0.740 inches   |
| Actuator Color:  |
| White single actuator  |
| Illuminated Actuator Color:  |
| Red single actuator and green single actuator  |
| Maximum Voltage Rating In Volts:   |
| 28.0 dc and 115.0 ac   |
| Mounting Surface To Terminal End Distance:   |
| 3.060 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Vertical split lens  |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, two positions momentary single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes |
| inductive ac and 1.500 amperes lamp ac   |

Precious Material And Location:

Contacts silver and contact surfaces gold

## NSN 5930-01-348-7198

Push Switch - Page 2 of 2



|   | Inal | אות | 10 | 110                | $\boldsymbol{\sim}$ | ao: |
|---|------|-----|----|--------------------|---------------------|-----|
| u | ııaı | JIE | 10 | $\boldsymbol{\nu}$ | CU                  | uc. |

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

12 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0