NSN 5930-01-348-7199

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-348-7199

view offilite at https://defobasegroup.com/hsh/5550-01-546-7155
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof
Overall Length:
3.060 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator and green single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
3.060 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes
inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contacts silver and contact surfaces gold

NSN 5930-01-348-7199

Push Switch - Page 2 of 2



			_	_			
 na	h	_	Го	116	~	\sim	ο.

Unable to decode and unable to decode

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0