

View Online at <https://aerobasegroup.com/nsn/5930-01-348-7200>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof

**Overall Length:**

3.060 inches

**Overall Height:**

0.740 inches

**Overall Width:**

0.740 inches

**Body Width:**

0.740 inches

**Body Height:**

0.740 inches

**Case Material:**

Metal

**Actuator Length:**

0.740 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.740 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Red single actuator and amber single actuator and blue single actuator and green single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

3.060 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Four-way split lens

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0