NSN 5930-01-348-7200

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-348-7200

Panel mounted
Hazardous Locations/environmental Protection:
Vibration resistant and shock resistant and salt spray resistant and moisture resistant and explosion proof
Overall Length:
3.060 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator and amber single actuator and blue single actuator and green single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
3.060 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Four-way split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes

Precious Material And Location:

Contacts silver and contact surfaces gold

inductive ac and 1.500 amperes lamp ac

NSN 5930-01-348-7200

Push Switch - Page 2 of 2



l	Inal	h	le	T٥	De	C	od	Α	•
·	, na	•			\mathbf{r}		v	_	

Unable to decode and unable to decode

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0